

MATERIAL SAFETY DATA SHEET

STATEMENT OF HAZARDOUS NATURE

Not classified as hazardous according to criteria of Worksafe Vanuatu.

COMPANY DETAILS

Pacific Suppliers Limited Lini Highway PO Box 541 Port Vila, VANUATU Telephone Number: (678) 25082 Fax Number: (678) 25256

IDENTIFICATION

Product Name: Other Names: Manufacturer's Product Code: UN Number: Dangerous Goods Class and Subsidiary Risk: Hazchem Code: Poisons Schedule: Use: CRYSTAL CLEAR

1CCL None Allocated

None Allocated None Allocated Concentrated window and glass cleaner

Physical Description/Properties

Appearance:	Blue neutral liquid	
Melting Point:	Below 0°C	
Vapour Pressure:	Not Available	
Specific Gravity:	1.0	
Flashpoint:	Not flammable	
Flammability Limits:	Not flammable	
Solubility in Water:	Miscible in all proportions	

7

Other Properties

pH (undiluted):

Ingredients:

All hazardous substances as defined by the NOHSC Code 1008 are listed by chemical name and CAS No. Other ingredients which are determined to be non-hazardous are listed by generic name or as "other ingredients determined not to be hazardous".

Chemical name:	CAS No:	Proportion:
Ethylene glycol monobutyl		
ether	111-76-2	Less than 10%
Corrosion inhibitor	-	Less than 1%
Dye	-	Less than 1%
Water	7732-18-5	To 100%

HEALTH HAZARD INFORMATION

Acute:

Swallowed: Irritating and nauseating. Considered to be moderately toxic.

Eye: Irritating.

Skin: Mildly irritating on prolonged contact by defatting skin. **Inhaled:** May cause dizziness or headache on prolonged exposure to concentrated vapour.

Chronic

Prolonged contact may cause skin irritation. Regular use of a barrier cream minimizes such irritation.

FIRST AID

Swallowed: Give a glass of water and consult a doctor. **Eye:** In case of contact with eyes, rinse immediately with plenty of water. **Skin:** Wash with water. **Inhaled:** Leave contaminated area.

FIRST AID FACILITIES: Eye wash. Fresh water.

ADVICE TO DOCTOR: If swallowed, treat for water soluble high boiling organic solvent of moderate toxicity.

PRECAUTIONS FOR USE

Exposure Standards: TWA for ethylene glycol monobutyl ether is 25 ppm.

Engineering Controls: When used according to directions, vapour concentrations are normally below the TLV and there is no special ventilation requirement. **Personal Protection:** Avoid contact with the skin and eyes.

Flammability: Not flammable or combustible.

SAFE HANDLING INFORMATION

Storage and Transport: No special precautions. Spills and Disposal: May be flushed to sewer with water but prevent, by any means available, larger spillages from entering storm-water drains or water courses. To contain spillage, absorb on vermiculite or similar absorbing material and collect in drums. Residues may be flushed away with water. *Fire/Explosion Hazard:* Not flammable but if spilt in a fire, wear full protective clothing.

OTHER INFORMATION

The Threshold Limit Value-Time Weighted Average (TLV-TWA) is the time-weighted average concentration for a normal 8 hour work day and a 40 hour week, to which nearly all workers may be repeatedly exposed, day after day, without adverse effect.

CONTACT POINT: Pacific Suppliers (678) 25082